

FIXTURE SPECIFICATIONS AWDES P20 40K MVOLT CLF AL5LU BK NF 20KV SERIES (AWDE3) ACRYLIC WASHINGTON POSTLITE LED PERFORMANCE PACKAGE (P20) 40W LUMENS (NOMINAL), 6,000 **COLOR TEMPERATURE (40K)** VOLTAGE (MVOLT) 120-277V HOUSING (CLF) **CLASSIC LEAF CASTING** OPTICS (AL5LU) TYPE V ACRYLIC LUNAR OPTIC FINISH (BK) BLACK FINIAL (NF) NO FINIAL SURGE PROTECTION (20KV) 20kV/10kA SURGE PROTECTION

POLE AND BASE SPECIFICATIONS				
WDA 12 F4J 17D C03 BK LAB GRD RP135A	12 F4J 17D C03 BK LAB GRD RP135A			
SERIES (WDA)	WADSWORTH ALUMINUM POLE			
POLE HEIGHT (12)	12FT			
SHAFT STYLE (F4J)	SHAFT, 4 IN DIA. FLUTED, 0.25 WALL			
BASE DIAMETER (17D)	17IN BASE, DIAMOND PATTERN BOLT CIRCLE			
POLE TOP MOUNT (C03)	TENON, 3.00 O.D. X 3IN TALL			
FINISH (BK)	BLACK			
BASE MOUNT (LAB)	LESS ANCHOR BOLT			
GROUND (GRD)	1/2 COPPER GROUNDING LUG			
ELECTRICAL RECEPTACLE (RP135A)	RECEPTACLE WITH SMALL, IN-USE WET LOCATION COVER (BLACK)			

DECORATIVE STREET LIGHT

NOT TO SCALE

The City Of Goshen

Department of Public Works & Safety Office of Engineering

204 East Jefferson, Suite 1 Street, Goshen, Indiana 46528 Phone: 574-534-2201 Fax: 574-533-8626 Web: goshenindiana.org

l	Date Approx	Date Approved By The City Of Goshen Board Of Public Works & Safety and Approved Revisions					
Γ	03/27/2025						
Γ							

CITY OF GOSHEN, INDIANA STANDARD DETAIL

J. Hoffman Drawing Number:	D. Sailor, P.E
l	106