



FIXTURE SPECIFICATIONS

AWDES P20 40K MVOLT CLF AL5LU BK NF 20KV

SERIES (AWDE3)	ACRYLIC WASHINGTON POSTLITE LED
PERFORMANCE PACKAGE (P20)	40W LUMENS (NOMINAL), 6,000
COLOR TEMPERATURE (40K)	4000K
VOLTAGE (MVOLT)	120-277V
HOUSING (CLF)	CLASSIC LEAF CASTING
OPTICS (AL5LU)	TYPE V ACRYLIC LUNAR OPTIC
FINISH (BK)	BLACK
FINIAL (NF)	NO FINIAL
SURGE PROTECTION (20KV)	20kV/10kA SURGE PROTECTION

POLE AND BASE SPECIFICATIONS

WDA 12 F4J 17D C03 BK LAB GRD RP135A

SERIES (WDA)	WADSWORTH ALUMINUM POLE
POLE HEIGHT (12)	12FT
SHAFT STYLE (F4J)	SHAFT, 4 IN DIA. FLUTED, 0.25 WALL
BASE DIAMETER (17D)	17IN BASE, DIAMOND PATTERN BOLT CIRCLE
POLE TOP MOUNT (C03)	TENON, 3.00 O.D. X 3IN TALL
FINISH (BK)	BLACK
BASE MOUNT (LAB)	LESS ANCHOR BOLT
GROUND (GRD)	1/2 COPPER GROUNDING LUG
ELECTRICAL RECEPTACLE (RP135A)	RECEPTACLE WITH SMALL, IN-USE WET LOCATION COVER (BLACK)

DECORATIVE STREET LIGHT

NOT TO SCALE